



## Declaration of Compliance

<b>Business Operator</b>	Vikan A/S Rævevej 1 DK-7800 Skive (+45) 96 14 26 00
<b>商品名</b>	1011x, 1013x & HyGo, 5700x用, グレー
製品名	100388
	
Plastic Material	Polypropylene, 98 % Thermoplastic elastomer (TPE), 98 %
<b>EU 準拠</b>	
Regulation (EC) No 1935/2004	In accordance with EU Commission Regulation no. 1935/2004 article 3, 11(5), 15 and 17 the product is intended for food contact. The product is marked with the "glass & fork" symbol on the packaging or on the product itself through moulding.
	
AP(89)1	All pigments in the masterbatch comply with resolution AP 89(1)
Regulation (EC) No 2023/2006	The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).
Regulation (EU) No 10/2011	<p>本製品の製造に使用されるモノマー及び添加剤は、食品と接触するプラスチック材料及び製品に関する欧州議会及び理事会規則（EU）第10/2011号（2011年1月14日）の改正後の附属書に記載されています。</p> <p>Monomers and/or additives with specific migration limit (SML) are used. The substances with a SML will not migrate in quantities that will exceed the SML, under the specified conditions of use. Upon request we will supply relevant information regarding these substances on a confidential basis.</p> <p>Vikan A/S does not use multi-layer materials or articles with a functional barrier.</p>
Regulations (EC) No 1333/2008 and (EC) No 1334/2008	This material contains intentionally added "dual use" additives for which restrictions or purity criteria are in place in accordance with Regulations (EC) 1333/2008 and (EC) 1334/2008. Upon request we will supply relevant information regarding these substances on a confidential basis.



<b>US FDA Compliance</b>	<p>All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) 21 CFR parts 170 to 199.</p> <p>The polymers and additives complies with FDA 21 CFR part 174, 175, 176, 177, 178, 181, 182, 184, or 186. Additives are cleared according to FDA 21 CFR Part 178 (Indirect food additives), are generally recognised as safe (GRAS), are prior-sanctioned food ingredients, or are cleared on basis of regulations for food additives of before 1958.</p>
<b>英国のコンプライアンス</b>	<p>この製品の材質はEUの食品に関する規制(2019 No. 704)に準拠しています。</p>
<b>Danish Compliance</b>	<p>The product complies with the Danish consolidation Act no. 681 of 25/05/2020.</p>
<b>Japanese Compliance</b>	<p>All substances (polymers, monomers and additives) used in Vikan products comply with Article 18(3) of the Japanese Food Sanitation Act and are listed in Tables 1 and 2 of Appendix 1 of the Positive List.</p>
<b>溶出試験 樹脂</b>	<p>Samples of the product, or a similar product made from identical plastic material, have been tested for overall migration according to the test conditions specified in (EU) 10/2011 for repeated use, and the article comply with the overall migration limit of 10 mg/dm<sup>2</sup> or 60 mg/kg.</p> <p>Test conditions for overall migration were OM0 (30 min at 40 °C)</p> <p>Food simulants used for overall migration were 50 % ethanol (simulant D1) and 3 % acetic acid (simulant B)</p> <p>Compliance with specific migration limits, and other restrictions, has been documented through testing, calculation or simulation.</p>
<b>Max ratio of food contact surface area to volume</b>	<p>2.1 dm<sup>2</sup>/100 ml</p>
<b>食品接触 タイプ</b>	<p>The product is suitable for contact with the following types of food under the intended and foreseeable conditions of use:</p> <ul style="list-style-type: none"><li><input checked="" type="checkbox"/> Aqueous</li><li><input checked="" type="checkbox"/> Acidic</li><li><input checked="" type="checkbox"/> Alcoholic</li><li><input type="checkbox"/> Fatty</li><li><input checked="" type="checkbox"/> Dry</li></ul>
<b>Food contact usage time and temperature</b>	<p>Any food contact conditions up to 40 °C for 30 min.</p>
<b>Non-food contact usage temperature</b>	<p>Minimum temperature: 0 °C Maximum temperature: 80 °C</p>

**General**

クリーニングツールは、使用前に適切に洗浄、消毒、滅菌する必要があります。

また、適切な除染薬品を適切な濃度・時間・温度のもとで使用して、使用後にはクリーニングツールを適切に洗浄、消毒、滅菌することも重要です。

クリーニングツールの汚染除去を適切に行うことで、微生物の増殖と交差汚染のリスクを最小限に抑え、クリーニングツールの効率と耐久性を最大限にすることが可能です。

最大洗浄温度: 120°C

当社は、関係当局に向けて、関係者の要求に応じて、関連書類を提出いたします。

ヴァイカン本社（Vikan A/S）では、デンマーク獣医食品管理局（DVFA）へ登録しており、定められた自主管理システムについてDVFAによる監査を受けています。

**Date**

2025/09/30

**Made By**

Marta Sztuka  
Materials and Compliance Specialist