

0703

Automatic Watertight Coupling, 1/2"(Q)



1/2" automatic watertight coupling with water stop when disconnected from quick coupling.

Technical Data

Item Number	0703
Couplings Size	1/2 "
Material	Chromium-plated brass Galvanized steel (DIN 1.09035)
Complies with FDA RegulationI CFR 21¹	No
Complies with REACH Regulation (EC) No. 1907/2006	Yes **
Complies with California Proposition 65	No
SCIP number	095b5bea-9314-4e2d- 987b-8726dbd84c43
Complies with Halal and Kosher	Yes
PFAS, Phthalates and BPA intentionally added	No
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	3180 Pcs
Quantity Per Layer (Pallet)	0 Pcs.
Box Length	335 mm
Box Width	180 mm
Box Height	85 mm
Length	160 mm
Width	67 mm
Height	40 mm
Net Weight	0.16 kg
Weight cardboard (Recycling symbol "20" PAP)	0.0117 kg
Tare total	0.0117 kg
Gross Weight	0.17 kg
Cubic metre	0.000429 M3
Max. cleaning temperature (Dishwasher)	80 °C
Max usage temperature (non food contact)	70 °C
Min. usage temperature³	-30 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Max. bars pressure	25 Bar
GTIN-13 Number	5705020007033
GTIN-14 Number (Box quantity)	15705020007030
Customs Tariff No.	74122000
Country of origin	Denmark

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling

ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.