

UST Hand Brush

176 mm, Hard, Green



Item Number: 38912

This ULTRA SAFE TECHNOLOGY (UST) Hand Brush comes with angled Filament Security Units for optimal cleaning of conveyor belts, production lines, machinery and food-preparation surfaces in high-risk areas. All UST brushes feature a unique bristle system that minimises the risk of contamination and bristle loss. The ergonomically designed brush block prevents slipping out of the hand and reduces wrist strain. The design and position of the Filament Security Units offer an effective surface contact and enables the user to apply hard pressure directly to the surface being cleaned. The angled bristles effectively clean in corners, junctions and other hard-to-reach areas.

General Information

Bristle Stiffness	Hard
Colour	Green
Material	Polypropylene, Polyester (PBT)
UNSPSC Code	47131605
Country of Origin	Denmark

Product Dimensions

Visible bristle length	37 mm
Product Length/Depth	176 mm
Product Width	65 mm
Product Height	57 mm
Net Weight	0.229 kg

Packaging & Shipping Details

Box Quantity	10 Pcs.
Quantity Per Layer (Pallet)	120 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	1080 Pcs.
Box Length/Depth	290 mm
Box Width	195 mm
Box Height	182 mm
Plastic Packaging (Recycling Symbol "4") LDPE per Pcs.	0.0026 kg
Cardboard Packaging (Recycling symbol "20" PAP) per Pcs.	0.0137 kg
Total Tare Weight	0.0163 kg
Gross Weight	0.25 kg
Cubic metre	0,000652 M3
GTIN-13 Number	5705020389122
GTIN-14 Number (Box quantity)	15705020389129

Compliance & Standard Details

Complies with (EC) 1935/2004 on food contact materials ¹	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21 ¹	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Complies with the European Brushware Federation (FEIBP) Charter	Yes
Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No

Usage Limits

Max. usage temperature (food contact)	80
Max usage temperature (non food contact)	100
Recommended sterilisation temperature (Autoclave)	121
Max. cleaning temperature (Dishwasher)	93 °C
Max. drying temperature	100
Min. usage temperature ³	-20
Max. pH-value in Usage Concentration	10.5 pH
Min. pH-value in usage concentration	2 pH

Design & Patent Registration Details

Design Registration No.	EU 002189654-001, GB 9002189654-001, EU 009198203, UK 623677E
Pat. Pending/Patent No.	EP2816930 validated in DE, FR, GB and DK. US9204712 EP2816929 validated in DE, FR, GB and DK. US9357831

Sustainability Details

Multimaterial Plastics Identification Code - "7"	Yes
--	-----

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact

3. Do not store the product below 0° Celsius.