

44012

Detail Brush, 8.1", Extra stiff, Green



Effectively clean around gaskets, rubber strips and joints on machinery, and conveyor belts with this compact Detail Brush.

Technical Data

Item Number	44012
Bristle stiffness	Extra stiff
Visible bristle length	0.6 "
Material	Polypropylene Polyester (PBT) Stainless Steel (AISI 304L)
Complies with (EC) 1935/2004 on food contact materials ¹	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation I CFR 21 ¹	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS, Phthalates and BPA intentionally added	No
Design Registration No.	EU 002364174-1-2, GB 90023641740001-2
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	4800 Pcs.
Quantity Per Layer (Pallet)	240 Pcs.
Box Length/Depth	9.4 "
Box Width	5.9 "
Box Height	3 "
Product Length/Depth	8.1 "
Product Width	0.8 "
Product Height	1.2 "
Net Weight	0.0661 lbs
Weight bag (Recycling Symbol "4") LDPE	0.01 lbs
Weight cardboard (Recycling symbol "20" PAP)	0.02 lbs
Total Tare Weight	0.02 lbs
Gross Weight	0.0904 lbs
Cubic Feet	0.0043 ft ³
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (food contact)	176 °F
Max usage temperature (non food contact)	212 °F
Min. usage temperature	-4 °F
Max. drying temperature	212 °F

Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705020440120
GTIN-14 Number (Box quantity)	15705020440127
Customs Tariff Number	96039091
Country of Origin ISO Code	DK
Country of Origin	Denmark

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact
3. Do not store the product below 32 °Fahrenheit.