44023

Detail Brush with heat resistant filaments, 8.1" Extra stiff, Blue







Brush for removing debris from heat sealers and other packing equipment. It is ideal for cleaning grills and frying pans when cleaned whilst still warm.

Technical Data

loonnour Butu	
Item Number	44023
Bristle stiffness	Extra stiff
Visible bristle length	0.4 "
Material	Polypropylene Polyester (PBT) Stainless Steel (AISI 304)
Complies with (EC) 1935/2004 on food contact materials ¹	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21 ¹	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with Halal and Kosher	Yes
PFAS intentionally added	No
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	4800 Pcs.
Quantity Per Layer (Pallet)	240 Pcs.
Box Length/Depth	10.2 "
Box Width	5.9 "
Box Height	3 "
Product Length/Depth	8.1 "
Product Width	0.8 "
Product Height	2.4 "
Net Weight	0.0661 lbs
Weight bag (Recycling Symbol "4") LDPE	0.01 lbs
Weight cardboard (Recycling symbol "20" PAP)	0.02 lbs
Total Tare Weight	0.02 lbs
Gross Weight	0.0904 lbs
Cubic Feet	0.0087 ft3
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (food contact)	212 °F
Max usage temperature (non food contact)	347 °F
Min. usage temperature	-4 °F
Max. drying temperature	212 °F
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705022000315

GTIN-14 Number (Box quantity)	15705028000323
Customs Tariff Number	96039091
UNSPSC Code	47131605
Country of Origin ISO Code	DK
Country of Origin	Denmark

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact

3. Do not store the product below 32 °Fahrenheit.