

UST Bench Brush

13", Medium, Orange



Item Number: 45857

This ULTRA SAFE TECHNOLOGY (UST) Bench Brush with Ultra Bristle Security is designed for effective removal of damp and wet particles from conveyor belts in high-risk areas. All UST brushes feature a unique bristle system that minimizes the risk of contamination and bristle loss.

General Information

| | |
|-------------------|--|
| Bristle stiffness | Medium |
| Color | Orange |
| Material | Polyester (PBT), Glass reinforced, Polypropylene |
| UNSPSC Code | 47131605 |
| Country of Origin | Denmark |

Product Dimensions

| | |
|------------------------|------------|
| Visible bristle length | 2.2 " |
| Handle/Grip Length | 140 mm |
| Handle/Grip Length | 5.51 " |
| Product Length/Depth | 13 " |
| Product Width | 1.4 " |
| Product Height | 5.3 " |
| Net Weight | 0.3968 lbs |

Packaging & Shipping Details

| | |
|--|----------------|
| Box Quantity | 10 Pcs. |
| Quantity per Pallet (80 x 120 x approx.180 cm) | 960 Pcs. |
| Quantity Per Layer (Pallet) | 80 Pcs. |
| Box Length/Depth | 15 " |
| Box Width | 11.4 " |
| Box Height | 5.3 " |
| Plastic Packaging (Recycling Symbol "4") LDPE per Pcs. | 0.01 lbs |
| Cardboard Packaging (Recycling symbol "20" PAP) per Pcs. | 0.05 lbs |
| Total Tare Weight | 0.07 lbs |
| Gross Weight | 0.4619 lbs |
| Cubic Feet | 0.0551 ft3 |
| GTIN-13 Number | 5705020458576 |
| GTIN-14 Number (Box quantity) | 15705020458573 |



Compliance & Standard Details

| | |
|---|-----|
| Complies with (EC) 1935/2004 on food contact materials ¹ | Yes |
| Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice | Yes |
| Complies with FDA Regulation CFR 21 ¹ | Yes |
| Complies with UK 2019 No. 704 on food contact materials | Yes |
| Meets the REACH Regulation (EC) No. 1907/2006 | Yes |
| Complies with California Proposition 65 | Yes |
| Complies with Halal and Kosher | Yes |
| PFAS intentionally added | No |

Usage Limits

| | |
|---|----------|
| Max usage temperature (food contact) | 176 °F |
| Max usage temperature (non food contact) | 176 °F |
| Recommended sterilisation temperature (Autoclave) | 249.8 °F |
| Max. cleaning temperature (Dishwasher) | 199.4 °F |
| Max. drying temperature | 212 °F |
| Min. usage temperature | -4 °F |
| Max. pH-value in Usage Concentration | 10.5 pH |
| Min. pH-value in usage concentration | 2 pH |

Design & Patent Registration Details

| | |
|-------------------------|--|
| Design Registration No. | EU 002189654-0001, EU 002650838-1-4, US D838995, GB 9002650830001-4, GB 900265505800001- |
| Pat. Pending/Patent No. | EP2816930 validated in DE, FR, GB and DK. US9204712 EP2816929 validated in DE, FR, GB and DK. US9357831 |

Sustainability Details

| | |
|--|-----|
| Recycling Symbol "7", Miscellaneous Plastics | Yes |
|--|-----|

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact

3. Do not store the product below 32 °Fahrenheit.

