

55004

Padholder, 230 mm, , Red



Secure cleaning pads, 5523, 5524 and 5525 with the stainless-steel hooks on this solid, durable and lockable pad holder. It is designed with a revolving neck to make cleaning under equipment as low as 12 cm above floor level possible. It can be used with any Vikan handle, enabling users to safely clean floors and walls, under equipment and the outside of tanks/containers.

Technical Data

Item Number	55004
Material	Polypropylene Stainless Steel (AISI 304) Nylon
Complies with (EC) 1935/2004 on food contact materials¹	No
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulationl CFR 21¹	Yes
Complies with UK 2019 No. 704 on food contact materials	No
Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS, Phthalates and BPA intentionally added	No
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	1040 Pcs
Quantity Per Layer (Pallet)	80 Pcs.
Box Length	375 mm
Box Width	295 mm
Box Height	140 mm
Length	230 mm
Width	95 mm
Height	75 mm
Net Weight	0.234 kg
Weight bag (Recycling Symbol "4") LDPE ≥ PCR 30%	0.0047 kg
Weight cardboard (Recycling symbol "20" PAP)	0.0227 kg
Tare total	0.0274 kg
Gross Weight	0.26 kg
Cubic metre	0.001639 M3
Recommended sterilisation temperature (Autoclave)	121 °C
Max. cleaning temperature (Dishwasher)	93 °C
Max usage temperature (food contact)	100 °C
Max usage temperature (non food contact)	100 °C
Min. usage temperature³	-20 °C
Max. drying temperature	120 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	8 pH
GTIN-13 Number	5705020550041
GTIN-14 Number (Box quantity)	15705020550048

Customs Tariff No.

39241000

Country of origin

Lithuania

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

3. Do not store the product below 0° Celsius.