

56892

# Lid for Bucket 5688, 1.58 Gallon(s), Green



Lid for Vikan Hygiene Bucket 5688x. The lid prevents foreign objects from falling into the bucket when used for storage. The rim in the middle of the lid makes buckets stackable.

# Technical Data

Item Number	56892
Material	Polypropylene
Recycling Symbol "5", Polypropylene (PP)	Yes
Complies with (EC) 1935/2004 on food contact materials <sup>1</sup>	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulationl CFR 21 <sup>1</sup>	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS, Phthalates and BPA intentionally added	No
Design Registration No.	EU 002364190-1-8, GB 90023641900001-8
Box Quantity	5 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	920 Pcs.
Quantity Per Layer (Pallet)	40 Pcs.
Box Length	11.4 "
Box Width	10.6 "
Box Height	3 "
Length	11.6 "
Width	9.8 "
Height	0.8 "
Net Weight	0.5534 lbs
Weight cardboard (Recycling symbol "20" PAP)	0.12 lbs
Tare Total	0.12 lbs
Gross Weight	0.6724 lbs
Cubic Feet	0.0521 ft <sup>3</sup>
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (food contact)	212 °F
Max usage temperature (non food contact)	212 °F
Min. usage temperature	-4 °F
Max. drying temperature	248 °F
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705020568923

<b>GTIN-14 Number (Box quantity)</b>	15705020568920
<b>Customs Tariff No.</b>	39241000
<b>Country of Origin</b>	Denmark
<b>Content Gallon</b>	1.58 Gallon(s)

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact
3. Do not store the product below 32 °Fahrenheit.