

70412

Deck Scrub, waterfed, 10.6", Extra stiff, Green



Easily clean heavily soiled areas such as abattoirs and meat processing plants with this rugged waterfed Deck Scrub, featuring highly-effective water distribution.

Technical Data

| | |
|---|---|
| Item Number | 70412 |
| Bristle stiffness | Extra stiff |
| Visible bristle length | 0.9 " |
| Connection | Threaded |
| Material | Polypropylene Polyester (PBT) Stainless Steel (AISI 304L) |
| Complies with (EC) 1935/2004 on food contact materials ¹ | Yes |
| Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice | Yes |
| Complies with FDA Regulationl CFR 21 ¹ | Yes |
| Complies with UK 2019 No. 704 on food contact materials | Yes |
| Meets the REACH Regulation (EC) No. 1907/2006 | Yes |
| Complies with California Proposition 65 | Yes |
| Complies with Halal and Kosher | Yes |
| PFAS, Phthalates and BPA intentionally added | No |
| Design Registration No. | EU 008554125-0005, UK 6139375 |
| Box Quantity | 10 Pcs. |
| Quantity per Pallet (80 x 120 x approx.180 cm) | 800 Pcs. |
| Quantity Per Layer (Pallet) | 80 Pcs. |
| Box Length/Depth | 15 " |
| Box Width | 11.4 " |
| Box Height | 6.9 " |
| Product Length/Depth | 10.6 " |
| Product Width | 3 " |
| Product Height | 3.7 " |
| Net Weight | 0.8598 lbs |
| Weight bag (Recycling Symbol "4") LDPE | 0.02 lbs |
| Weight cardboard (Recycling symbol "20" PAP) | 0.05 lbs |
| Total Tare Weight | 0.07 lbs |
| Gross Weight | 0.9275 lbs |
| Cubic Feet | 0.068 ft3 |
| Recommended sterilisation temperature (Autoclave) | 249.8 °F |
| Max. cleaning temperature (Dishwasher) | 199.4 °F |
| Max usage temperature (food contact) | 176 °F |
| Max usage temperature (non food contact) | 212 °F |
| Min. usage temperature | -4 °F |

| | |
|---|----------------|
| Max. drying temperature | 212 °F |
| Min. pH-value in usage concentration | 2 pH |
| Max. pH-value in Usage Concentration | 10.5 pH |
| GTIN-13 Number | 5705020704123 |
| GTIN-14 Number (Box quantity) | 15705020704120 |
| Customs Tariff Number | 96039099 |
| Country of Origin ISO Code | DK |
| Country of Origin | Denmark |

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

3. Do not store the product below 32 °Fahrenheit.