Condensation squeegee, 15.7", Green







Designed to effectively remove condensation from ceilings and pipes during production, this Condensation Squeegee features drain holes that allow condensation to be collected safely in a bottle or drained away through an attached hose.

Technical Data

Item Number	77162
Connection	Threaded
Material	Polypropylene TPE Rubber
Recycling Symbol "7", Miscellaneous Plastics	Yes
Complies with (EC) 1935/2004 on food contact materials ¹	No
Complies with UK 2019 No. 704 on food contact materials	No
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS, Phthalates and BPA intentionally added	No
Pat. Pending/Patent No.	EP2384681 validated in DE, FR and GB. DK177048
Box Quantity	3 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	288 Pcs.
Quantity Per Layer (Pallet)	18 Pcs.
Box Length/Depth	17.5 "
Box Width	10.2 "
Box Height	4.3 "
Product Length/Depth	15.7 "
Product Width	5.1 "
Product Height	3.1 "
Net Weight	0.5225 lbs
Weight bag (Recycling Symbol "4") LDPE	0.03 lbs
Weight cardboard (Recycling symbol "20" PAP)	0.08 lbs
Total Tare Weight	0.11 lbs
Gross Weight	0.6327 lbs
Cubic Feet	0.147 ft3
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (non food contact)	212 °F
Min. usage temperature	-4 °F
Max. drying temperature	248 °F
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705020775628
GTIN-14 Number (Box quantity)	15705020775625

Customs Tariff Number	96039099
Country of Origin ISO Code	DK
Country of Origin	Denmark

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

3. Do not store the product below 32 °Fahrenheit.