

# HyDrive Adaptor x 2

Pcs., Ø20 mm, 55 mm, Black



**Item Number: 87509**

The adaptor connects directly to a drill using a hexagonal bit and allows compatible Vikan pipe cleaning brushes to be threaded onto the adaptor. This configuration enables power-assisted cleaning for:

- Valves
- Fittings
- Threads
- Recesses
- Complex equipment geometries

Can be used with the following products:

- 538050x
- 538063x
- 538077x
- 538090x
- 5380103x
- 7035x

## General Information

<b>Colour</b>	Black
<b>Material</b>	Polyamide, Stainless Steel (AISI 304)
<b>Country of Origin</b>	Denmark

## Product Dimensions

<b>Product Diameter</b>	20 mm
<b>Product Length/Depth</b>	55 mm
<b>Product Width</b>	30 mm
<b>Product Height</b>	55 mm
<b>Net Weight</b>	0.046 kg

## Packaging & Shipping Details

<b>Box Quantity</b>	5 Pcs.
<b>Quantity per Pallet (80 x 120 x approx.180 cm)</b>	2400 Pcs.
<b>Quantity Per Layer (Pallet)</b>	120 Pcs.
<b>Box Length/Depth</b>	240 mm
<b>Box Width</b>	150 mm
<b>Box Height</b>	75 mm
<b>Plastic Packaging (Recycling Symbol "4") LDPE per Pcs.</b>	0.005 kg
<b>Cardboard Packaging (Recycling symbol "20" PAP) per Pcs.</b>	0.017 kg
<b>Total Tare Weight</b>	0.022 kg

## Item Number: 87509

Gross Weight	0 kg
Cubic metre	9.1E-05 M3
GTIN-13 Number	5705022053397
GTIN-14 Number (Box quantity)	15705028053404
Customs Tariff Number	39269097

## Compliance & Standard Details

Complies with (EC) 1935/2004 on food contact materials <sup>1</sup>	Yes
Complies with EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
Complies with FDA Regulation CFR 21 <sup>1</sup>	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
PFAS intentionally added	No
Phthalates intentionally added	No
Bisphenols intentionally added	No

## Technical Data

Hex Bit Size	6 mm
CA Marked	Yes
CE Marked	Yes

## Usage Limits

Recommended sterilisation temperature (Autoclave)	121 °C
Min. usage temperature <sup>3</sup>	-20 °C
Max. drying temperature	100 °C