

880703

Coupling with Hose Nozzle and Shut-Off Valve, 1/2" (Q)



1/2" automatic watertight coupling with water stop when disconnected from quick coupling.

Low lead content.

Technical Data

Item Number	880703
Couplings Size	1/2 "
Complies with FDA Regulation CFR 21 ¹	Yes
Complies with REACH Regulation (EC) No. 1907/2006	Yes
Complies with California Proposition 65	Yes
Complies with Halal and Kosher	Yes
PFAS, Phthalates and BPA intentionally added	No
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	4800 Pcs
Quantity Per Layer (Pallet)	240 Pcs.
Box Length/Depth	240 mm
Box Width	150 mm
Box Height	75 mm
Product Length/Depth	73 mm
Product Width	28 mm
Product Height	28 mm
Net Weight	0.157 kg
Weight bag (Recycling Symbol "4")	0.0015 kg
Weight cardboard (Recycling symbol "20" PAP)	0.009 kg
Total Tare Weight	0.0105 kg
Gross Weight	0.17 kg
Cubic metre	5.7E-05 M3
Max. cleaning temperature (Dishwasher)	80 °C
Max usage temperature (non food contact)	70 °C
Min. usage temperature ³	-30 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Max. bars pressure	25 Bar
GTIN-13 Number	5705022046658
GTIN-14 Number (Box quantity)	15705028046666
Customs Tariff Number	74122000
Country of Origin ISO Code	DK
Country of Origin	Denmark

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.

1. The product is suitable for use with water only and not for direct food contact.