

9341

## SafeOne, Back Flow Prevention, 1/2" (Q)



For use with foam sprayers 9303x and, 9305x as protection against chemical backflow into the water supply system. Click hose with "Q" coupling directly on the SafeOne.

Click directly on the water tap if you have tap coupling, 0700 mounted.

# Technical Data

Item Number	9341
Couplings Size	1/2 "
VA Approval	
Material	Chromium-plated brass
Complies with REACH Regulation (EC) No. 1907/2006	Yes **
Complies with California Proposition 65	No
Box Quantity	8 Pcs.
Quantity per Pallet (80 x 120 x approx.180 cm)	1680 Pcs
Quantity Per Layer (Pallet)	1 Pcs.
Box Length/Depth	250 mm
Box Width	175 mm
Box Height	70 mm
Net Weight	0.382 kg
Recommended sterilisation temperature (Autoclave)	60 °C
Max. cleaning temperature (Dishwasher)	60 °C
Max usage temperature (non food contact)	60 °C
Min. usage temperature <sup>3</sup>	5 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Min. Bars pressure	10 Bar
Max. bars pressure	25 Bar
GTIN-13 Number	5705022045798
GTIN-14 Number (Box quantity)	15705028045805
Customs Tariff Number	84818099
Country of Origin ISO Code	DK
Country of Origin	Denmark

\*\* Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.