

16200

Bracket for bucket, 5686, 5688 and 5692, 370 mm



This bracket allows Vikan's 6L bucket 5688x and 12L bucket 5686x to hang when filled and it can store both Vikan's 6L 5688x , 12L 5686x and 20L 5692x buckets upside-down after cleaning.

A small hook on the bracket allows for lid or brush storage, ensuring optimal hygiene levels.

Technical Data

| | |
|--|----------------------------|
| Item Number | 16200 |
| Material | Stainless Steel (AISI 304) |
| Complies with UK 2019 No. 704 on food contact materials | No |
| Complies with REACH Regulation (EC) No. 1907/2006 | Yes |
| Complies with California Proposition 65 | Yes |
| Complies with Halal and Kosher | Yes |
| PFAS, Phthalates and BPA intentionally added | No |
| Box Quantity | 1 Pcs. |
| Quantity per Pallet (80 x 120 x 180-200 cm) | 851 Pcs |
| Quantity Per Layer (Pallet) | 0 Pcs. |
| Box Length | 480 mm |
| Box Width | 80 mm |
| Box Height | 65 mm |
| Length | 370 mm |
| Width | 80 mm |
| Height | 50 mm |
| Net Weight | 0.23 kg |
| Weight cardboard (Recycling symbol "20" PAP) | 0.08 kg |
| Tare total | 0.08 kg |
| Gross Weight | 0.31 kg |
| Cubic metre | 0.00148 M3 |
| Recommended sterilisation temperature (Autoclave) | 121 °C |
| Max. cleaning temperature (Dishwasher) | 93 °C |
| Max usage temperature (non food contact) | 100 °C |
| Min. usage temperature³ | -20 °C |
| Min. pH-value in usage concentration | 2 pH |
| Max. pH-value in Usage Concentration | 10.5 pH |
| Gtin-13 Number | 5705020162008 |
| Customs Tariff No. | 83025000 |
| Country of origin | China |

New equipment should be cleaned, disinfected, sterilised and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.